

FRESAS PARA PERFILAR MATERIALES DUROS DE DIAMANTE SINTERIZADO CON METAL

- Eje o vástago de Ø 6 mm para esmeriladoras de hasta **30.000 RPM**

| Forma | Diámetro | Altura | Referencia | P.V.P. |
|-------|----------|--------|------------|--------|
| 21 | 16,0 | 8,7 | F52.10070 | |
| 22 | 8,0 | 8,0 | F52. 10090 | |
| 23 | 4,0 | 16,0 | F52. 10110 | |
| 24 | 8,0 | 16,0 | F52. 10130 | |
| 25 | 12,5 | 15,0 | F52. 10040 | |
| 26 | 10,0 | 30,0 | F52. 10050 | |
| 27 | 12,0 | 20,0 | F52. 10060 | |
| 28 | 13,0 | 13,0 | F52. 10080 | |
| 29 | 25,0 | 6,0 | F52. 10100 | |
| 38 | 12,0 | 17,0 | F52. 10180 | |
| 39 | 14,0 | 12,0 | F52.10190 | |
| | | | | |

Eje de Ø 3 mm hasta **85.000RPM**

| Forma | Diámetro | Altura | Referencia | P.V.P. |
|-------|----------|--------|------------|--------|
| 60 | 3,5 | 8,0 | F52.10200 | |
| 61 | 3,5 | 7,0 | F52.10210 | |
| 62 | 3,0 | 3,0 | F52.10220 | |
| 64 | 10,0 | 6,0 | F52.10240 | |

